

16ch/24ch NEWEST Network NVR 1 * HI3535 CPU Product Launch NVR Standalone



1.5U size H.264 High profile compression

FLA-NVR70816B: 4*3M/8*1080P/16*960P(720P)/24*D1,30fps 3M decoding

FLA-NVR72432B: 8ch*5M/16ch*3M/ 24ch*1080P/32ch*960P,30fps 5M decoding

Support:

Arabic,Czech,English,Finnish,Greek,Indonesian,Italian,,Japanese,Portuguese,Russian,Thai, T-Chinese,S-Chinese,Turkish,Brazilian,Bulgarian,Farsi,French,German,Hebrew,Hungarian,P olish,Romanian,Spanish,Swedish,Vietnamese

Support smart mobile and network (IE&Firefox&Safari&Chrome) real time remotely monitoring, such as iPhone, Blackberry, Android, and windows mobile.

Main Features

- *H.264/MJPEG dual codec decoding
- *Video access: 8ch*5M/16ch*3M/ 24ch*1080P/32ch*960P etc.
- * HDMI / VGA simultaneous video output
- *Support Multi-brand network cameras
- * ONVIF Version 2.0 conformance
- * Support 1 SATA HDD up to 4TB, 2 USB2.0

Technical Parameter:

Model	FLA-NVR70816B	FLA-NVR72432B
SYSTEM		
Main Processor	1XHI3515	1XHI3535
Operating System	Embedded LINUX	
System Resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup	
Preview	1/4/9(8ch)/16	1/4/8/16/24/32
User Interface	support 16-bit true color graphical menu interface and mouse operation	
Control Device	Front panel, USB mouse, IR remote control, CMS	
VIDEO		
Video Standards	PAL 625 line,50 f/s; NTSC 525 line,60 f/s	

Video Compression	H.264 High profile	
Display quality	monitor:D1;VGA,HDMI:HD	
Play quality	3.0mega pixel/1080P/720P	5M/3M/1080P/720P
Video Access	4*3M/8*1080P/16*960P(720P)access to the storage	8*5M/16*3M/ 24*1080P/32*960P to the storage
Motion detect	support	
AUDIO		
Audio Compression	G711A	
Bidirectional Talk	Support	
RECORD&PLAYBACK		
Recording Mode	Manual>Alarm>Video Detection>Continuous	
Playback	1ch(3M);2ch(1080P);4ch(960P/720P) real-time	2ch*5M/4ch*3M/4ch*1080P/8ch*960P Real-time
Search Mode	Time/calendar/event/channel search	
Storage & Backup		
Space Occupation	Video: 1080p 80G/day/ch, 720p 26G/day/ch, 960H 24G/day/ch, D1 16~20G/day/ch ; Audio: 691.2M/day/channel	
HDD Management	HDD Network	
Backup Mode	Network backup, USB HDD,USB writer, SATA writer	
INTERFACE		
Video Input	4ch 3M /8ch 1080P /16ch 960P(720P) etc.	8ch*5M/16ch*3M/ 24*1080P/32*960P
Video Output	2ch BNC output, 1ch VGA output, 1ch HDMI	
Audio Input	1 channel	
Audio Output	1 channel	
Relay Output	1 channel	
Net Interface	RJ-45 10M/100M/1000M	
PTZ Control	1 RS485, 1 RS232	
3G/WIFI	Support	
USB Interface	2* USB2.0 port for mouse and backup	
Hard Disk	1SATA port(Max 1 x 4T)	
Environment		
Power Supply	12V/2A	
Power Consumption	<10W	
Working Temperature	0-55	
Working	10%-90%	

Humidity	
Atmosphere Pressure	86kpa-106kpa
Dimension	350(L)* 295mm(W)* 45mm(H)
ONVIF	Support