

Newest 8CH 1080P 16CH 720P HDMI P2P HVR / NVR Hybrid Digital Cloud CCTV



1.5U size H.264 **High profile** compression

FLA-NVR0808B : **8\*1080P/8\*720P,30fps 1080P decoding**

FLA-NVR0816B : **8\*1080P/16\*720P,30fps 1080P decoding**

Support:

Arabic,Czech,English,Finnish,Greek,Indonesian,Italian,,Japanese,Portuguese,Russian,Thai, T-Chinese,S-Chinese,Turkish,Brazilian,Bulgarian,Farsi,French,German,Hebrew,Hungarian,P olish,Romanian,Spanish,Swedish,Vietnamese

Support smart mobile and network (**IE&Firefox&Safari&Chrome**) real time remotely monitoring, such as iPhone, Blackberry, Android, and windows mobile.

**Main Features**

- \*H.264/MJPEG dual codec decoding
- \*Video Access: 8\*\*1080P/16\*720P etc.
- \* HDMI / VGA simultaneous video output
- \*Support Multi-brand network cameras
- \* ONVIF Version 2.0 conformance
- \* Support 2 SATA HDDS up to 8TB, 2 USB2.0

**Technical Parameter:**

Model	FLA-NVR0808B	FLA-NVR0816B
<b>SYSTEM</b>		
Main Processor	1 X HI3521	1 X HI3531
Operating System	Embedded LINUX	
System Resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup	
Preview	1/4/9	1/4/8/16
User interface	support 16-bit true color graphical menu interface and mouse operation	
Control device	Front panel, USB mouse, IR remote control	
<b>VIDEO</b>		
Video Standards	PAL 625 line,50 f/s; NTSC 525 line,60 f/s	
Video Compression	H.264 High profile	

Display quality	monitor:D1;VGA,HDMI:HD	
Play quality	1080P/960P/720P	1080P/960P/720P
Video Access	8*1080p or 8*720P	8*1080P or 16*720P
Motion Detection	Support	
TV Output Adjustment	Adjust TV output color & display zone	
<b>AUDIO</b>		
Audio Compression	G711A	
Bidirectional Talk	Support	
<b>RECORD &amp; PLAYBACK</b>		
Recording Mode	Manual>Alarm>Video Detection>Continuous	
Playback	1*1080p	1*1080p
Search Mode	Time/Date, Alarm, Motion Detection & exact search(accurate to second)	
<b>STORAGE &amp; BACKUP</b>		
Space Occupation	Video: 1080p 80G/day/ch, 720p 26G/day/ch, 960H 24G/day/ch, D1 16~20G/day/ch ; Audio: 691.2M/day/channel	
HDD Management	Hard disk hibernation technology, HDD faulty alarm & Raid(Redundancy)	
Backup Mode	Network download/Flash stick	
<b>INTERFACE</b>		
Video Input	N/A	
Video Output	2ch BNC output, 1ch VGA output, 1ch HDMI	
Audio Input	1 channel	
Audio Output	1 channel	
Alarm Input	16 channel	
Relay Output	4 channel	
Net Interface	RJ-45 10M/100M	RJ-45 10M/100M/1000M
PTZ Control	1 RS485, 1 RS232	
3G/WIFI	Support	
USB Interface	2* USB2.0 port for mouse and backup	
Hard Disk	2 SATA port(Max 2 x 4T)	
<b>ENVIROMENT</b>		
Power Supply	12V/2A	
Power Consumption	<10W	
Working Temperature	0-55	
Working Humidity	10%-90%	
Atmosphere Pressure	86kpa-106kpa	
Dimension	295 x 225 x 60mm	
ONVIF	Support	