

Security 1M,1.3M,2M megapixel surveillance HD CVI Box Camera



Features:

1. 1/3" 1M,1.3M,2Megapixel CMOS
2. 25/30fps@720P,960P,1080P
3. High speed, long distance real-time transmission
4. HD and standard definition switch
5. OSD Menu, control over coaxial cable
6. WDR, Day/Night(ICR), 3D-DNR, Auto Iris
7. DC12V

Specification:

Model Number	FLA-BC100WA-HC	FLA-BC130WA-HC	FLA-BC200WA-HC
Image Sensor	1/2.9" 1Megapixel CMOS	1/3" 1.3Megapixel CMOS	1/3" 2Megapixel CMOS
Effective Pixels	1280(H)×720(V)	1280(H)×960(V)	1920(H)×1080(V)
Electronic Shutter	1/50s~1/100,000s	PAL: 4/25s~1/45,000s; NTSC: 4/30~1/54,000s	1/3s~1/100,000s
Video Frame Rate	25fps@720P, 30fps@720P	1280×720@25 fps; 1280×720@30 fps; 1280×720@50 fps; 1280×720@60 fps	1920'1080@25fps; 1920'1080@30fps; 1280'720@25 fps; 1280'720@30 fps; 1280'720@50 fps; 1280'720@60 fps
Synchronization	Internal		
Min. Illumination	0.01Lux@F1.2(0Lux IR LED on)		
Video Output	1-channel BNC HDCVI high definition video output/ CVBS		

	standard definition video output (Can switch)
Max. IR LEDs Length	80m, Smart IR
Day/Night	Auto(ICR)/B&W/Color
Noise Reduction	3D/2D
OSD Menu	Support
Lense	Not included
Power Supply	DC12V±10%
Power Consumption	Max 6W
Working Environment	-30°C~+60°C Humidity is less than 95%(no condensation)
Transmission Distance	Over 500m via 75-3 coaxial cable
Weatherproof Protection	IP66
Packed Dimensions(W×D×H)	122x62x64mm
Weight(kg)	0.45KG