

HD CVI IR Bullet Camera HD 1MP/1.3MP/2MP IR Security Digital Camera



Main Features:

- > 1/3" 1M,1.3M,2Megapixel CMOS
- > 25/30/50/60fps@720P,960P,1080P
- > High speed, long distance real-time transmission
- > HD and standard definition switch.
- > OSD Menu, control over coaxial cable
- > Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- > 6mm fixed lens (4mm,8mm optional)
- > Max. IR LEDs length 20m, Smart 36pcs IR Leds
- > IP66, DC12V

Technical Parameter:

Model Number	FLA-BQ100WHL-HC	FLA-BQ130WHL-HC	FLA-BQ200WHL-HC
Image Sensor	1/2.9" 1Megapixel CMOS	1/3" 1.3Megapixel CMOS	1/3" 2Megapixel CMOS
Effective Pixels	1280(H)×720(V)	1280(H)×960(V)	1920(H)×1080(V)
Electronic Shutter	1/50s~1/100,000s	PAL: 4/25s~1/45,000s; NTSC: 4/30~1/54,000s	1/3s~1/100,000s
Video Frame Rate	25fps@720P, 30fps@720P	1280×720@25 fps; 1280×720@30 fps; 1280×720@50 fps; 1280×720@60 fps	1920'1080@25fps; 1920'1080@30fps; 1280'720@25 fps; 1280'720@30 fps; 1280'720@50 fps; 1280'720@60 fps
Synchronization	Internal		
Min. Illumination	0.01Lux@F1.2(0Lux IR LED on)		
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)		
Max. IR LEDs Length	20m, Smart 36pcs IR leds		
Day/Night	Auto(ICR)/B&W/Color		
Noise Reduction	3D/2D		
OSD Menu	Support		
Focal length	6MM (4mm,8MM optional)		
Power Supply	DC12V±10%		
Power Consumption	Max 6W		
Working Environment	-30°C~+60°C Humidity is less than 95%(no condensation)		

Transmission Distance	Over 500m via 75-5 coaxial cable
Weatherproof Protection	IP66
Packed Dimensions(W×D×H)	250x130x150mm
Weight(kg)	1.35KG