

Outdoor 1080P / 960P/720P IR 1M/1.3M/2M HD CVI Waterproof Camera Varifocal Lens



Main Features:

- >1/3" 1M,1.3M,2Megapixel CMOS
- >25/30/50/60fps@720P,960P,1080P
- >High speed, long distance real-time transmission
- >HD and standard definition switch.
- >OSD Menu, control over coaxial cable
- >Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- >2.8-10mm Varifocal lens (4-9mm, 3.5-8mm optional)
- >Max. IR LEDs length 20m, Smart 36Pcs IR leds
- >IP66, DC12V

Technical Parameter:

| Model Number | FLA-QJ100WBX-HC | FLA-QJ130WBX-HC | FLA-QJ200WBX-HC |
|---------------------|--|---|---|
| Image Sensor | 1/2.9" 1Megapixel CMOS | 1/3" 1.3Megapixel CMOS | 1/3" 2Megapixel CMOS |
| Effective Pixels | 1280(H)×720(V) | 1280(H)×960(V) | 1920(H)×1080(V) |
| Electronic Shutter | 1/50s~1/100,000s | PAL: 4/25s~1/45,000s; NTSC: 4/30~1/54,000s | 1/3s~1/100,000s |
| Video Frame Rate | 25fps@720P, 30fps@720P | 1280×720@25 fps ; 1280×720@30 fps; 1280×720@50 fps ; 1280×720@60 fps | 1920'1080@25fps; 1920'1080@30fps; 1280'720@25 fps; 1280'720@30 fps; 1280'720@50 fps; 1280'720@60 fps |
| Synchronization | Internal | | |
| Min. Illumination | 0.01Lux@F1.2(0Lux IR LED on) | | |
| Video Output | 1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch) | | |
| Max. IR LEDs Length | 20m, Smart 36pcs IR leds | | |
| Day/Night | Auto(ICR)/B&W/Color | | |
| Noise Reduction | 3D/2D | | |

| | |
|---------------------------|--|
| OSD Menu | Support |
| Focal length | 2.8-10MM (3.5-8MM,4-9MM optional) |
| Power Supply | DC12V±10% |
| Power Consumption | Max 6W |
| Working Environment | -30°C~+60°C Humidity is less than 95%(no condensation) |
| Transmission Distance | Over 500m via 75-5 coaxial cable |
| Weatherproof Protection | IP66 |
| Packed Dimensions(W×D×H) | 220x120x115mm (Bracket included) |
| Weight(kg) | 1.45KG |