

Outdoor 1920P/ 1080P/ 960P IR 3M/2M/1.3M IP Camera Varifocal Lens



Main Features:

- *H. 264 image compression, 1920P,1080P,960P Resolution
- *Built-in Web server, IE client support
- *Day and night Surveillance, F8 36pcs IR LED, 50m IR distance
- *Max. 30fps image transmission
- *TCP/IP, ARP, RARP, ICMP, DHCP, FTP, HTTP, and SMTP protocol support
- *Remote snap shot and video recording
- *Self-contained FTP server & E-mail sending function
- *Free multi-screen management software.
- *Applicable in schools, banks, communications, posts and telecommunications, electric power system, video conference, high-class hotels, multinational enterprises, chain stores, home security etc.

Specification:

Model Number	FLA-QJ130WHZ	FLA-QJ200WHZ	FLA-QJ300WHZ
Image Sensor	HI3518C+AR0130	HI3516C+IMX222	A5S88+AR0330
Resolution	1.3M	2M	3M
Min illumination	Color:0.6Lux (F1.2, AGC ON),0 LUX with IR Black/white: 0.08Lux (F1.2, AGC ON), 0LUX with IR		
shutter	1/50(1/60)s to 1/100,000s		
lens	HD professional lens 2.8-12mm F1.2 (Varifocal lens) (4-9mm,		

	5-15mm,6-60mm Optional)
Day & night	IR-CUT filter double light switch ,automatically shift from color to B/W, 36pcs F8 Leds,Night vision30- 50M
Video compression	H. 264 High Profile, support dual stream, AVI format; support 0.1M~6Mpbs bit rate adjustable; support 1~30fps adjustable.
Video bit rate	100Kbps~6Mbps
Resolution	Main stream: 2048 x 1536P, 1920*1080p,1280*960p
Frame Rate	50Hz: 25fps (1920*1080) 11fps(2560*1920)/60Hz: 30fps (1920*1080) 15fps(2560*1920)
Image setting	Saturation, brightness, contrast can be adjusted via client side or IE browser
Storage	Network
Intelligent alarm	Motion detect, video lost, network break, IP conflict, storage device full or error
Protocol	1 * RJ45, 10/100M; Support TCP/IP HTTP/RTSP/FTP/PPPOE/DHCP/DNS/DDNS/NTP/UPnP
Basic	Support WEB remote configuration, OSD, motion detect, alarm input active to record, snapshot
	CMS, mobile(iPhone/Blackberry/Android/Symbian/windows), MYEYE(multiple devices management system), SDK
	ONVIF Support
Communicating	1pcs RJ45 10M/100M self adaptive Ethernet interface
Video output	Support CVBS video output and overlying DDNS, user name, password and other info.
POE	Support(Optional)
Working condition	-50~60 degree. humidity less than 90%(non-condensing)
Packed Dimensions	310x150x140MM(Bracket not measured)
Power supply	DC12V 2A
Weight	2.5kg